

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A communication system, comprising:

a communication device including:

an accessing unit capable of accessing web pages;

an interface unit having an opening, a first circuit and a second circuit;

and

a data acquiring unit that acquires data via the interface unit;

a portable operation member removably insertable into the opening of the interface unit, the portable operation member including a memory that stores first access data corresponding to a first predetermined web page; and

an operation detecting unit configured to detect that the portable operation member is inserted into the opening of the interface unit when the first circuit activates and
~~in a state that the portable operation member is already inserted into the opening of the interface unit;~~ that the portable operation member is mechanically operated by a user when
the second circuit activates;

~~wherein the data acquiring unit automatically acquires~~ acquiring the first
access data from the memory when the operation detecting unit detects that the second circuit
activates in response to a detection, detected by the operation member, that the portable
~~operation member is directly operated by a user and the accessing unit automatically accesses~~
accessing the first predetermined web page based on the first access data acquired by the
acquiring unit.

2. (Currently Amended) The communication system according to claim 1, further comprising:

a transmitting system that transmits the first access data contained in the memory to the accessing system when the operation detecting unit detects that the portable operation unit is mechanically operated by the user; and

wherein:

the transmitting system is included in the portable operation member;

the transmitting system determines whether a predetermined condition is satisfied when the operation detecting unit is operated detects that the portable operation member is mechanically operated by the user; and

the transmitting system transmits the first access data from the memory to the accessing system when the predetermined condition is satisfied.

3. (Previously Presented) The communication system according to claim 2, wherein:

the portable operation member includes:

a counting system that counts the number of times the first access data is transmitted from the memory to the accessing system; and

wherein the transmitting system determines that the predetermined condition is satisfied if the number of times counted by the counting system is less than a predetermined number, the transmitting system determining the predetermined condition is not satisfied if the number of times counted by the counting system has reached the predetermined number.

4. (Currently Amended) The communication system according to claim 3, wherein:

the communication device includes:

a count inquiry system that transmits a count inquiry signal inquiring the number counted by the counting system to the portable operation member; and

a count notifying system that notifies the number counted by the counting system based on a count response signal which is transmitted by the portable operation member in response to the count inquiry signal transmitted thereto; and

the portable operation member includes a count response system that outputs the count response signal to the communication device in response to the count inquiry signal transmitted from the communication device.

5. (Currently Amended) The communication system according to claim 4, wherein the count inquiry system transmits the count inquiry signal when the first access data is transmitted from the memory of the portable operation member.

6. (Currently Amended) The communication system according to claim 4, wherein ~~the communication device includes an attachment detection system that detects the insertion of the operation member into the opening, the count inquiry system outputting~~ outputs the count inquiry signal when the attachment detection system operation detecting unit detects the insertion of the portable operation member.

7. (Currently Amended) The communication system according to claim 3, wherein:

the communication device includes:

an allowed number inquiry system that transmits an allowed number inquiry signal inquiring an allowed number of times that the first access data stored in the memory is allowed to be transmitted from the memory of the portable operation member; and

an allowed number notifying system that notifies the allowed number based on a response signal which is transmitted by the portable operation member in response to the allowance number inquiry signal transmitted thereto, and

the portable operation member includes a response system that outputs the response signal to the communication device in response to the allowed number inquiry signal transmitted from the communication device.

8. (Currently Amended) The communication system according to claim 7, wherein the allowed number inquiry system transmits the allowed number inquiry signal when the first access data is transmitted from the memory of the portable operation member.

9. (Currently Amended) The communication system according to claim 7, wherein ~~the communication device includes an attachment detection system that detects the insertion of the operation member into the opening,~~ the allowed number inquiry system ~~outputting~~ outputs the allowed number inquiry signal when the ~~attachment detection system~~ operation detecting unit detects the insertion of the portable operation member.

10. (Currently Amended) The communication system according to claim 2, wherein:

the memory contains second access data indicating a second web page ; and

the transmitting system transmits the second access data stored in the memory to the accessing system if the predetermined condition is not satisfied when the operation detecting unit detects ~~that the~~ the mechanical operation of the portable operation unit ~~is mechanically operated by the user.~~

11. (Currently Amended) The communication system according to claim 1, wherein the communication device includes:

a device side detecting system that detects if the operation detecting unit is operated; and

a notification system that notifies that the first access data is not received because the predetermined condition is not satisfied when the first access data is not transmitted from the memory of the portable operation member for a predetermined period.

12. (Currently Amended) The communication system according to claim 1, further comprising:

a transmitting system that transmits the first access data contained in the memory to the accessing system when the operation detecting unit detects ~~that the~~ the mechanical operation of the portable operation unit is mechanically operated by the user; and

wherein:

the transmitting system is included in the communication device;

the transmitting system determines whether a predetermined condition is satisfied when the operation detecting unit detects ~~that the~~ the mechanical operation of the portable operation unit is mechanically operated by the user; and

the transmitting system transmits the first access data contained in the memory to the accessing system when the predetermined condition is satisfied.

13. (Currently Amended) The communication system according to claim 12, wherein:

the memory stores a transmission number representing a number of times that the first access data is transmitted by the transmitting system;

the communication device includes:

a device side detection system that detects if the operation detecting unit detects ~~that the~~ the mechanical operation of the portable operation unit is mechanically operated by the user; and

a readout system that reads out the transmission number from the memory when the device side detection system detects that the operation detecting unit detects ~~that the~~ the mechanical operation of the portable operation unit is mechanically operated by the user;

the transmitting system determines that the predetermined condition is satisfied if the readout transmission number has not reached a predetermined number, the transmitting system determining that the predetermined condition is not satisfied when the readout transmission number has reached the predetermined number; and

the communication device further includes a rewriting system that increases the transmission number by one when the first access data is transmitted to the accessing system.

14. (Previously Presented) The communication system according to claim 13, wherein the communication device includes a notification system that notifies the transmission number.

15. (Currently Amended) The communication system according to claim 13, wherein:

the memory contains an allowed number of times by which the first access data is allowed to be transmitted;

the readout system reads out the transmission number and the allowed number from the memory when the device side detection system detects if the operation detecting unit detects that the mechanical operation of the portable operation unit is mechanically operated by the user; and

the transmitting system determines that the predetermined condition is satisfied if the readout transmission number has not reached the allowed number, the transmitting system determining that the predetermined condition is not satisfied when the readout transmission number has reached the allowed number.

16. (Previously Presented) The communication system according to claim 12, wherein:

the memory contains second access data indicating a second web page; and

the transmitting system transmits the second access data stored in the memory to the accessing system if the predetermined condition is not satisfied when the portable operation member is mechanically operated.

17. (Currently Amended) A communication system, comprising:

a communication device including:

an accessing unit capable of accessing web pages;

a plurality of interface units, each interface unit having an opening, a first circuit, and a second circuit;

a plurality of data acquiring units that acquire data via the interface units;

a plurality of portable operation members, each portable operation member removably insertable into the openings of the interface units, each of the plurality of portable operation members including a memory that stores access data corresponding to a predetermined web page;

an operation detection unit configured to detect that one of the portable operation members is inserted into an opening of an interface unit when the first circuit activates and, ~~in a state that one of the plurality of portable operation members is already inserted into the opening of one of the plurality of interface units,~~ that the one of the plurality of portable operation members is mechanically operated by a user when the second circuit activates;

~~wherein the data acquiring units automatically acquire~~ acquiring the access data from the memory when the operation detecting unit detects that the second circuit activates ~~in response to a detection, detected by the one of the plurality of operation members, that the one of the plurality of portable operation members is mechanically operated by a user~~

and the accessing unit automatically ~~accesses~~ accessing the predetermined web page based on the access data acquired by the acquiring unit.

18-25. (Canceled)

26. (Currently Amended) A computer-readable storage medium storing a computer-executable program for allowing a communication system to access a predetermined web page, the program comprising:

instructions for controlling ~~detecting the an operation of a detecting unit to detect an~~, the operation caused by insertion of a portable operation member into an opening of an interface unit of the communication system and a mechanical operation of the portable operation member after insertion into the opening of the interface unit;

instructions for transmitting access data contained in a memory of the portable operation member to an accessing system of the communication system upon the detection of the mechanical operation of the portable operation member ~~when the operation of the detecting unit is detected~~; and

instructions for causing the accessing system to access the predetermined web page based on the access data transmitted from the memory of the portable operation member.

27. (Previously Presented) The communication system according to claim 1, wherein the memory comprises a ROM, the ROM storing the first access data.

28. (Previously Presented) The communication system according to claim 13, wherein the memory comprises a ROM and a RAM, the ROM storing the first access data and the RAM storing the transmission number.

29. (Currently Amended) A portable operation member capable of being inserted into a communication device, the portable operation member including a memory storing first

access data corresponding to a first predetermined web page, the communication device comprising:

an accessing unit capable of accessing web pages;

an interface unit having an opening to insert the portable operation member, a first circuit and a second circuit;

a data acquiring unit that acquires data from the memory via the interface unit;

and

an operation detecting unit configured to detect that the portable operation member is inserted into the opening of the interface unit when the first circuit activates and
~~in a state that the portable operation member is already inserted into the opening of the interface unit,~~ that the portable operation member is mechanically operated by a user when the second circuit activates;

~~wherein the data acquiring unit automatically acquires~~ acquiring the first
access data from the memory when the operation detecting unit detects that the second circuit
activates ~~in response to a detection, detected by the operation detecting unit, that the portable~~
~~operation member is mechanically operated by a user and the accessing unit automatically~~
~~accesses~~ accessing the first predetermined web page based on the first access data acquired by
the acquiring unit.

30. (Previously Presented) The communication system according to claim 1,
wherein the mechanical operation of the portable operation member includes a depression of
the portable operation member by the user.

31. (Previously Presented) The communication system according to claim 17,
wherein the mechanical operation of the portable operation member includes a depression of
one of the plurality of portable operation members by the user.

32. (Currently Amended) The computer-readable storage medium according to claim 26, wherein the instructions for controlling ~~detecting the mechanical operation of the~~ detecting unit to detect a mechanical operation of the portable operation member include instructions for detecting a depression of the portable operation member.

33. (Previously Presented) The communication device according to claim 29, wherein the mechanical operation of the portable operation member includes a depression of the portable operation member by the user.